TITLE OF THE INVENTION

EXPOSURE APPARATUS AND ALIGNING METHOD

5   FIELD OF THE INVENTION

The present invention relates to an aligning apparatus preferably applicable to reticle alignment in a semiconductor exposure apparatus.

10   BACKGROUND OF THE INVENTION

In a semiconductor exposure apparatus, the accuracy of alignment of reticle and wafer is significant performance which directly influences the apparatus capability. In the exposure apparatus, a

15   circuit pattern drawn on a reticle must be precisely overlaid on each shot area pattern on a wafer, thus different circuit patterns must be overlaid in multiple layers on the wafer. To obtain such high overlay accuracy, it is necessary to always accurately align

20   the reticle and the wafer. Generally, in the exposure apparatus, the respective wafer and reticle substrates are aligned with their respective stages for high-accuracy alignment therebetween. For this purpose, the accuracy of alignment of the reticle and wafer stages

25   is also significant.

For example, alignment of a reticle with the reticle stage is made by overlaying a reticle mark

1

provided on a reticle lower surface on a reference mark
provided on the reticle stage and measuring the
overlaid marks. That is, the reticle is placed on the
reticle stage, then the reticle and/or the reticle

5   stage is moved to a position where predetermined
relative positional relation can be obtained between
the reticle marks and the reference mark, thereby
alignment is made.

Conventionally, a system to realize the above

10   alignment has a construction as shown in Fig. 1. A
reticle 5, supplied from a reticle transfer robot 1, is
aligned based on outer form shape by using thrust pins
3 in a reticle holder 2. Then the reticle 5 is
supplied by a reticle exchange hand 4 onto a reticle

15   stage 10, and is aligned with the reticle stage 10.
Numerals 20 and 21 denote measurement cameras and
illumination LEDs for image sensing the reticle mark
and a reference mark. An image processing unit 31
measures the positions of these marks using the

20   obtained image data. The result of position
measurement is used for reticle alignment. In this
example, the result of measurement is reflected in a
reticle stage driver 11 through a control unit 32. A
reticle holder 12 on the reticle stage 10, in the

25   aligned state, holds the reticle, thereby the alignment
of the reticle is realized.

However, in an initial status of the above

2

alignment, if the positions of the reference mark and
the reticle mark are unknown, a search for the mark
positions must be performed, thus the throughput of the
apparatus is seriously delayed. Generally, the
5   position of the reference mark of the stage can be
grasped by the apparatus itself, however, the position
of the reticle mark differs by reticle. Accordingly,
to improve the throughput of the apparatus, rough
alignment called prealignment is performed so as to
10   find the reticle mark position.

Japanese Published Unexamined Patent Application
No. 2000-349022 proposes a system to efficiently
realize this prealignment. According to the system,
the prealignment is performed in parallel with setup
15   processing such as inspection of reticle contamination
and generation of inventory, thereby the throughput is
improved. However, in this system, as a 4-cell
detector fixed to a rotary part of a reticle exchange
hand is used as means for measurement of prealignment,
20   the accuracy of alignment is the same on the reticle
supply side and the reticle stage side. Further, in
this system, it is difficult to attain high accuracy.

SUMMARY OF THE INVENTION

25

The present invention has its object to realize
substrate alignment with high alignment accuracy so as

3

to attain high throughput.

According to the present invention, the foregoing object is attained by providing an exposure apparatus which performs alignment on a substrate on first and

5   second stages, and performs predetermined exposure processing using the substrate aligned on the second stage, comprising: a first alignment unit to detect a position of a mark on a substrate placed on the first stage by using a first image sensing unit, and perform

10   alignment on the substrate based on the result of detection; a transfer unit to transfer the substrate, aligned by the first alignment unit, from the first stage onto the second stage; and a second alignment unit to detect the position of the mark on the

15   substrate placed on the second stage by using a second image sensing unit having higher magnification than that of the first stage, and perform alignment on the substrate based on the result of detection.

Also, according to another aspect of the present

20   invention, there is provided an aligning method for aligning a substrate by using first and second stages, comprising: a first alignment step of detecting a position of a mark on a substrate placed on the first stage by using a first image sensing unit, and

25   performing alignment on the substrate based on the result of detection; a transfer step of transferring the substrate, aligned at the first alignment step,

4

from the first stage to the second stage by a transfer

unit; and a second alignment step of detecting the

position of the mark on the substrate placed on the

second stage by using a second image sensing unit

5   having higher magnification than that of the first

stage, and perform alignment on the substrate based on

the result of detection.

Other features and advantages of the present

invention will be apparent from the following

10   description taken in conjunction with the accompanying

drawings, in which like reference characters designate

the same name or similar parts throughout the figures

thereof.

15   BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated

in and constitute a part of the specification,

illustrate embodiments of the invention and, together

20   with the description, serve to explain the principles

of the invention.

Fig. 1 is a schematic diagram showing reticle

transfer and a reticle aligning mechanism in a general

exposure apparatus;

25   Fig. 2 is a schematic diagram showing the reticle

aligning mechanism according to a first embodiment of

the present invention;

Fig. 3 is a schematic diagram showing the structure of a prealignment stage according to the first embodiment;

Fig. 4 is a graph showing calculation of correction amount according to the first embodiment;

Fig. 5 is a schematic diagram showing the reticle aligning mechanism according a second embodiment of the present invention;

Fig. 6 is a schematic diagram showing the structure of the prealignment stage according to the second embodiment;

Fig. 7 is a graph showing the calculation of correction amount according to the second embodiment; and

Fig. 8 is a flowchart showing an exposure processing procedure according to the first embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described in detail in accordance with the accompanying drawings.

In the embodiment described below, the present invention is applied to a reticle alignment mechanism in an exposure apparatus. In the exposure apparatus, prealignment for a reticle to be aligned is performed in parallel with an exposure processing operation,

thereby reticle exchange time is reduced, and high throughput is realized.

<First Embodiment>

5   Fig. 2 is a schematic diagram showing a reticle aligning mechanism according to a first embodiment of the present invention. As described above, the present embodiment is applied to an exposure apparatus, however, for the purpose of detailed explanation of the reticle

10   aligning mechanism, elements of the exposure apparatus such as a projection optical system and a wafer stage are omitted in Fig. 2.

        In addition to the conventional construction as shown in Fig. 1, a stage 30 for prealignment, image

15   sensing units 40 and illumination LEDs 41 constituting an image sensing mechanism are provided. Note that the reticle transfer robot 1 is omitted from the figure. Further, the image sensing units 20 and the illumination LEDs 21 will be referred to as a first

20   image sensing mechanism, and the image sensing units 40 and the illumination LEDs 41, as a second image sensing mechanism. The prealignment stage 30 is a stage driven by, e.g., an XYθ 3-axis linear motor. The image sensing units 20 and 40 are e.g. CCD cameras. The

25   first image sensing mechanism (20, 21) and the second image sensing mechanism (40, 41) are fixed on the same non-movable element (not shown). Thus the reference

7

positions of the both image sensing units (20, 40) are fixed to predetermined measurement coordinate positions such as measurement centers of cameras.

The reference positions on the reticle holder 12

5   on the reticle stage 10 are brought into correspondence with the reference position of the image sensing units 20, and the reference positions on the reticle holder 2 on the prealignment stage 30 are brought into correspondence with the reference positions of the

10   image sensing units 40. Thus the relative positions of the reticle holder 2 and the reticle holder 12 are clearly obtained.

Fig. 8 is a flowchart showing reticle alignment processing in the exposure apparatus according to the

15   first embodiment.

First, at step S1, a reticle to be used in exposure processing is transferred onto the reticle holder 2 by the robot 1. At step S2, alignment is performed based on outer form shape of the reticle with

20   the thrust pins 3. At step S3, detection of reticle marks and rough alignment (prealignment) are performed by the second image sensing mechanism (40, 41) and the prealignment stage 30. These reticle transfer processing at step S1 and the prealignment processing

25   at steps S2 and S3 can be performed in parallel with alignment of reticle on the reticle stage 10 and exposure processing (steps S11 and S12).

8

At the timing of reticle exchange, the process proceeds from step S4 to step S5, at which the pre-aligned reticle is transferred from the prealignment stage 30 to the reticle stage 10 by the reticle

5   exchange hand 4. When the reticle transfer by the reticle exchange hand 4 has been completed, as a used reticle (reticle that was subjected to exposure) is placed on the prealignment stage 30, the used reticle is unloaded by the robot 1 (not shown in Fig. 2) at

10   step S6. Thereafter, the process returns to step S1, at which rough alignment is performed on the next reticle. On the other hand, on the reticle stage 10, accurate alignment is performed on the reticle transferred at step S5. That is, at step S11, high-

15   accuracy reticle alignment is realized by the first image sensing mechanism (20, 21). Then at step S12, the reticle stage 10 moves the aligned reticle to an exposure processing position, and exposure processing is performed on the reticle. When the exposure has

20   been completed, the reticle is returned to the reticle alignment position (the position of reticle transfer from the prealignment stage 30) at step S13, and the reticle exchange hand 4 is notified that transfer is possible.

25   The reticle exchange hand 4 unloads the used reticle from the reticle stage 10 in response to the notification, and loads a prealigned reticle onto the

9

reticle stage 10 (steps S4 and S5).

Hereinbelow, the reticle alignment will be described in more detail.

First, the reticle transferred by the robot 1 to
5   the reticle holder 2 at step S1 is aligned based on the outer form shape with the thrust pins at step S2. Fig. 3 shows the structure of the reticle holder 2. The reticle alignment with the thrust pins is made by, e.g., with 3 pins 3a as reference pins, pressing 2 pins 3b to
10   reticle end surfaces. The purpose of the alignment with the thrust pins is bringing the reticle into a predetermined range without measurement of reticle marks position, for efficient prealignment by image sensing. For this purpose, it is desirable that the
15   positional relation between the 2 sides to abut against the 3 reference pins 3a and the reticle marks are obtained in advance as reticle information. After the alignment based on the outer form shape with the thrust pins, the reticle holder 2 holds the reticle by e.g.
20   vacuum clamping the lower surface of the reticle, then the process proceeds to the prealignment at step S3.

To detect the reticle marks aligned based on the outer form shape with the thrust pins without search, the image sensing unit 40 has a wide-view detection
25   range in consideration of the accuracy of the thrust pins 3 and reticle-mark drawing error in each reticle, so as to reliably detect the reticle marks after the

execution of step S2. The reticle marks are measured
by the second image sensing mechanism (40, 41), and the
reticle marks are aligned to reference positions
(predetermined camera measurement coordinate positions)
5   42 and 43.

The correction amount in alignment is calculated
as shown in Fig. 4. "XYθ" is calculated from the
relative positions of the measurement coordinates 42,
43 as the reference position measured by the image
10   sensing units 40 and the reticle marks 44 and 45. Note
that "O'" denotes a center of line segment connecting
the reticle marks 44 and 45. The value "XYθ" is
reflected in the prealignment stage 30 through the
control unit 34, thereby the prealignment stage moves
15   so as to bring the reticle marks to the reference
positions. Thus the prealignment is completed.

After the above rough alignment (prealignment),
the reticle is transferred onto the reticle stage 10 by
the reticle exchange hand 4 (step S5). At this time, if
20   the amount of driving of the reticle exchange hand 4 is
always the same, the positions of the reticle marks on
the reticle transferred onto the stage 10 can be
measured in approximately the same positions each time.
Accordingly, the second image sensing mechanism (40,
25   41) and the reticle holder 2 have reference positions
as reference prealignment positions to bring the
reticle marks into a predetermined positional range

(the view range of the first image sensing mechanism)
upon the reticle transfer by the reticle exchange hand
4. By this arrangement, on the reticle stage 10, as
the reticle marks are positioned within the view of the
5   first image sensing mechanism (20, 21) without search
of reticle marks, high-accuracy alignment can be
immediately performed. Preferably, the reference
positions in the reticle holder 2 are brought into
correspondence with e.g. the camera center upon
10 assembly. Further, if such previous setting is
difficult, shift amounts from the camera center may be
used as offset amounts. The coordinate positions
shifted by the offset amounts can be set as reference
positions.

15   When the reticle has been transferred by the
reticle exchange hand 4, the reticle marks are image-
sensed and measured on the reticle stage 10, thus the
reticle is finally aligned (step S11). On the reticle
stage 10 side, as the mark positions have been obtained
20 by the previous prealignment, high-accuracy reticle
alignment can be performed without search for reticle
marks by the first image sensing mechanism (20, 21)
having a narrower view and higher magnification than
the second image sensing mechanism (40, 41). Actually,
25 a shift occurs due to mechanical contact or the like
upon transfer by the reticle exchange hand 4, the shift
amount can be corrected as an offset amount on the

12

prealignment stage 30 or the reticle stage 10 side.
Thus the reticle alignment can be performed without
losing the effect of the prealignment.

Note that the reticle marks measured at step S11
may by the same as or may be different from the reticle
marks measured at step S3. That is, it may be arranged
such that reticle marks for prealignment are different
from reticle marks for final alignment for improvement
in accuracy. In this case, the relative positions of
the reticle marks used at step S11 and the reticle
marks used at step S3 are clearly obtained in advance,
thereby alignment can be performed without search for
reticle mark as in the case of the above embodiment.

Further, after the reticle alignment, the reticle
stage 10 moves to the exposure position for execution
of exposure processing, while the next reticle is
transferred to the reticle holder 2. As described
above, as prealignment is performed with the measured
coordinate points as reference positions, the reticle
marks can be detected without reticle stage.
Accordingly, the prealignment at steps S2 and S3 can be
completed during the exposure at step S12. As a result,
after the completion of exposure, when the reticle
stage 10 returns to the alignment position, only the
reticle exchange by the reticle exchange hand 4 and the
reticle alignment at step S11 are performed. Thus, the
reticle alignment can be very efficiently performed.

13

Note that in the above embodiment, the reticle alignment has been described, however, the present invention is applicable to wafer alignment.

As described above, the aligning apparatus
5 according to the first embodiment performs alignment on a first stage (prealignment stage 30, thrust pins 3 and reticle holder 2) and a second stage (reticle stage 10). The apparatus has a first alignment unit (thrust pins 3, image processing unit 33, control unit 34, second image
10 sensing mechanism 40, 41) to perform alignment on a substrate placed on the first stage to bring marks (reticle marks) on the substrate to predetermined positions, a transfer device (reticle exchange hand 4) to transfer the substrate (reticle) from the first
15 stage to the second stage, and a second alignment unit (image processing unit 31, control unit 32, first image sensing mechanism 20, 21) to perform alignment with higher accuracy than that of the first alignment unit on the substrate placed on the second stage. The
20 destinations of the marks on the substrate by the transfer device are known, and as the positions of the marks on the substrate are brought to the predetermined positions by the first alignment unit, the marks can be placed to positions appropriate to execution of
25 alignment by the second alignment unit upon transfer of the substrate to the second stage. Thus the alignment processing by the second alignment unit can be quickly

14

performed. In a case where the alignment apparatus is applied to an exposure apparatus, predetermined processing such as exposure processing is performed using the substrate placed on the above second stage.

5   Then the alignment by the first alignment unit can be performed on a substrate newly placed on the first stage during execution of alignment by the second alignment unit and/or predetermined processing such as exposure processing.

10   In this arrangement, as prealignment can be completed during execution of predetermined processing such as exposure processing, processing time for substrate alignment can be reduced, and the throughput of the apparatus can be improved.

15   Further, the first alignment unit includes processing to perform alignment based on the outer form shape of the substrate. As the positions of the reticle marks can be brought into a predetermined range by using the outer form shape, the apparatus structure

20   can be simplified, and the processing speed can be increased. Note that it is necessary to previously obtain relative distances between the positions of reference points of the outer form shape and the mark positions to be measured.

25   Further, according to the first embodiment, the above first alignment unit performs alignment based on the outer form shape of substrate (by using the thrust

15

pins), then measures the marks of the substrate by image sensing thereby performs alignment of the substrate. Especially, in the first embodiment, the first stage is driven based on the result of

5   measurement of the image-sensed marks of the substrate such that the marks are brought to predetermined reference positions (the reticle stage 30 is moved in the XYθ direction).

     Further, in the above-described transfer device,

10   to reflect the result of alignment performed on the first stage (prealignment) on the second stage with high accuracy, the substrate holding position on the first stage (reticle holder 2) and the substrate holding position on the second stage (reticle holder

15   12) are linked with each other. As the relative positional relation between the reference positions of the respective holders are clearly obtained, efficient alignment without search for substrate marks can be realized on the second stage. Note that since the

20   linkage between the positions of the both reticle holders greatly influences the accuracy of mark alignment, it is preferable that reference positions of the image sensing mechanisms in the respective reticle holders are used. Further, as a mechanism to chuck the

25   substrate in the reticle holder, a well-known chuck mechanism such as an electrostatic chuck or a vacuum chuck can be employed.

<div align="center">16</div>

Further, the above linkage is made for the

purpose of clearly obtaining the position to the

reference position of the first image sensing mechanism

(20, 21), upon the transfer of the substrate, pre-

5   aligned to the reference positions of the second image

sensing mechanism (40, 41) in the reticle holder 2, by

the reticle exchange hand 4 to the reticle holder 12.

As long as the relative position is clearly obtained,

even if a positional shift occurs upon reticle transfer,

10   the shift amount is used as an offset amount to the

reference position of the reticle holder 2. Thus the

substrate can be approximately accurately transferred

to the reference position of the reticle holder 12

(first image sensing mechanism 20, 21).

15

<Second Embodiment>

In the first embodiment, prealignment is realized

by driving the prealignment stage 30 in the $XY\theta$

direction. In the second embodiment, prealignment is

20   realized by fine driving of thrust pins, thereby the

structure can be simplified.

Fig. 5 shows the reticle aligning mechanism

according the second embodiment. The present

embodiment is also applied to an exposure apparatus.

25   As in the case of the above embodiment shown in Fig. 2,

for the purpose of detailed explanation of the reticle

aligning mechanism, elements of the exposure apparatus

such as a projection optical system and a wafer stage are omitted in Fig. 5. The difference from Fig. 2 is that the prealignment stage 30 is not used but thrust pins 50 (pins 50a to 50d as shown in Fig. 6) which can

5   be finely driven are used for prealignment.

Fig. 6 shows the details of the reticle thrust pins 50 in Fig. 5. The thrust pin 50a, provided on the Y axis of the measurement coordinate system, can be finely driven in the X direction; the thrust pins 50b

10   and 50c, provided on the X axis of the measurement coordinate system, can be finely driven in the Y direction; and the thrust pin 50d, having a spring mechanism between the pin and the driving portion, can absorb fine driving of the pins 50a, 50b and 50c and

15   distortion of the outer form shape of the reticle.

The entire flow of the exposure processing including prealignment according to the second embodiment is as described in the first embodiment (Fig. 8). In the second embodiment, the prealignment

20   processing at steps S2 and S3 is different.

The prealignment according to the present embodiment is performed as follows. First, in a status where the reticle is placed on a stage for prealignment, the thrust pins 50 are moved to predetermined positions

25   so as to abut against the reticle, thus the reticle is aligned based on outer form shape.

Next, the reticle marks 44 and 45 are measured by

18

the first image sensing mechanism (40, 41) while the
reticle in the above status is held. In the second
embodiment, the alignment correction amount is
calculated as shown in Fig. 7. The correction amount X

5   is reflected in the driving of the pin 50a; the
correction amount Y1, in the driving of the pin 50b;
and the correction amount Y2, in the driving of the pin
50c, through the image processing unit 33 and the
control unit 34. As a result, the reticle marks 44 and

10   45 can be aligned with the reference positions 42 and
43. In the first embodiment, a rotational component is
corrected in the θ directional driving axis, however,
in the second embodiment, the rotational component is
corrected by independently moving the pins 50b and 50c

15   by Y1 and Y2. All the correction amounts can be
obtained from the differences between the reference
positions 42, 43 and the reticle mark positions 44, 45.
Further, as the correction directions and the operation
directions of the driven parts are the same, the

20   structure is intuitive.

     In the second embodiment, as actuators are
employed only for the 4 axes of thrust pins,
commonality of driving units for thrust pins and
prealignment can be realized, thereby further

25   downsizing and weight reduction in comparison with the
first embodiment can be attained. Further, in the
second embodiment, 2 measurement reference points and 2

19

axes of Y-axis driving units are employed on the
assumption of rotational shift, however, in a case
where correction of rotational shift is unnecessary, 1
measurement reference point and 1 Y-axis driving unit

5   may be employed, thereby further downsizing and weight
reduction can be made.

Further, in the sequence of the entire apparatus
operation, merely the processing at steps S2 and S3 is
changed, thus the flow of reticle exchange is the same

10   as that in the first embodiment. That is, the
prealignment at steps S2 and S3 can be completed during
exposure. Then, after the completion of exposure, when
the reticle stage 10 returns to the alignment reference
position, only the reticle exchange by the reticle

15   exchange hand 4 and the final alignment at step S1 are
performed thereby the reticle alignment is completed.
Thus, very efficient reticle alignment can be realized.

As described above, according to the second
embodiment of the first embodiment, the first stage,

20   including the prealignment stage 30, the thrust pins 3
and the reticle holder 2, is constituted with the
thrust pins 50 and the reticle holder 2. The image
sensing and measurement are performed on the reticle
marks, then based on the result of measurement, the

25   reticle is further aligned based on the outer form
shape (by using thrust pins) such that the marks are
brought to predetermined reference positions. In the

second embodiment, as the prealignment stage 30 can be

omitted, the structure can be simplified.

As described above, according to the above

respective embodiments, reticle alignment and

5   prealignment can be realized with high alignment

accuracy, without search for mark, and further,

prealignment in parallel with an exposure operation can

be realized. Accordingly, the entire throughput of the

exposure apparatus can be improved.

10   As described above, according to the present

invention, substrate alignment with high alignment

accuracy to attain high throughput can be realized.

As many apparently widely different embodiments

of the present invention can be made without departing

15   from the spirit and scope thereof, it is to be

understood that the invention is not limited to the

specific embodiments thereof except as defined in the

appended claims.

20